

MARSTEK

Power Anywhere & Anytime



MARSTEK VENUS B

800W/1.5kW 2kWh Plug-in AC-Coupled ESS



Efficient Bidirectional Power

1.5kW bidirectional power for worry-free energy



Reliable Backup Protection

1.5kW Backup Power, Peak at 1.8kW



Quick Installation

Plug & Play in 5 Minutes



Compact Design

2kWh Usable Capacity per Unit



MARSTEK AI

AI-Driven Energy Optimization



Built for Durability

6000+ Cycles LFP Cells | IP65 | 10-Year Warranty

Marstek Energy Co., Limited

Add: BLDG#A, Changfang Industrial Park, No.2 Guihua 5th Road, Pingshan District, Shenzhen, Guangdong, China

Tel: 86-755-28398778

Email: market@marstekenergy.com

Web: www.marstekenergy.com



SPECIFICATIONS



Model	MARSTEK VENUS B
Host Battery Parameters	
Rated Voltage	6.4V
Capacity	2009.6Wh (314Ah*2S)
Cycle Life	>6000 (25°C)
Battery Cell Type	LiFePO ₄
Depth of Discharge (DoD)	90%
AC Input	
Rated Input Power	1.5kVA
Working Phase	L/N/PE
Rated Grid Voltage / Frequency	230V/50Hz
Rated Grid Input Current	6.52A
Power Factor	>0.99 (default), 0.8 lagging...0.8 leading (adjustable)
THDi	<3%
AC Output	
Rated Output Power	800VA/1.5kVA
Working Phase	L/N/PE
Rated Grid Voltage / Frequency	230V/50Hz
Rated Grid Output Current	3.48A/6.52A
Power Factor	>0.99 (Default), 0.8 lagging...0.8 leading (Adjustable)
THDi	<3%
Backup (Off-Grid)	
Rated Input/Output Power	1.5kVA
Peak Input/Output Power	1.8kVA (60s)
Rated Input/Output Current	6.52A
Rated Voltage / Frequency	230V/50Hz
THDu (Linear Load)	<3%
Efficiency	
Battery Side – AC Side Maximum Efficiency	>88%
Protection	
Protection Class	I
Overvoltage Withstand Level	DC II / AC III
General	
Ambient Temperature Range	-20°C ~ +60°C (Storage: -30°C ~ +85°C)
Dimensions	395*(455+5)*(86+9.5)mm
Relative Humidity	≤95%
IP Rating	IP65
Cooling Method	Natural Cooling
Maximum Operating Altitude	2000m
Grid-Connected Port	MST-grid Port
Off-Grid Port	European Socket
Display	LED
Communication Interfaces	Bluetooth, Wi-Fi